

AGRIMAX TERIS - Tekniska specifikationer



Description

Dagens kraftfulla skördemaskiner kräver däck som håller för tung utrustning och större laster, utan att skada grödan. BKT gör sitt yttersta för att förse dig med banbrytande radialdäck som förbättrar skörden. AGRIMAX TERIS är rätt val av partner för hela din verksamhet. Utmärkt dragförmåga och hög lastkapacitet är avgörande faktorer som ger den bästa prestandan vid alla skördearbeten. Det speciella skyddet i sidoväggen och förstärkt däckskuldra ökar motståndskraften – och förlänger produktens livslängd – även under krävande förhållanden och om det finns stubb på åkern.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Bomullsmaskin • Skördemaskin

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 520/85 R 42 |
| LI/SS | 168 D |

Dimensions US Standard

| | |
|------------------------------|--|
| Usa code | 94044634 |
| Section Width (inch) | 20.3 |
| Overall Diameter (inch) | 76.8 |
| Static Loaded Radius (inch) | 35 |
| Rolling Circumference (inch) | 230.4 |
| Rim Rec | DW 16 L |
| Rim Alt | W15L ; DW15L ; DD16L ; W16L ; DD18L ; DW18L ; W18L |
| ECE | E4-106R-001829 |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 55 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 4080 | 4820 | 5560 | 6170 | 6920 | 7540 | 8770 | 10010 | 11240 | 12350 | - |
| 30 | 4290 | 5060 | 5840 | 6480 | 7260 | 7910 | 9200 | 10500 | 11810 | 12960 | - |
| 25 | 4460 | 5280 | 6100 | 6770 | 7580 | 8260 | 9610 | 10960 | 12310 | 13520 | - |
| 20 | 4700 | 5540 | 6390 | 7100 | 7960 | 8660 | 10090 | 11510 | 12930 | 14200 | - |
| 15 | 4840 | 5710 | 6590 | 7320 | 8200 | 8940 | 10390 | 11860 | 13330 | 14640 | - |
| 5 | 6120 | 7230 | 8330 | 9260 | 10370 | 11300 | 13150 | 15000 | 16850 | 18520 | - |
| 5 Cyc* | - | - | - | - | - | - | - | - | - | - | 20990 |

* - * 10 Cyc application inflation pressure to be increased by 0.8 bar.

Printed on 5/21/2024 12:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..