

## AGRIMAX TURF RT 333 - Tekniska specifikationer



### Description

AGRIMAX TURF RT 333 (R-3+) är ett radialdäck designat för små traktorer som används till trädgårdsskötsel, i fruktodlingar och på vingårdar. Den rundade däcksuldran ger låg jordpackning och gör däckets extremt skonsamt mot marken. Det unika, extra djupa däcktäcket (R-3+) och specialdesignen med riktat mönster ger utmärkt dragförmåga på både åkern och vägen, liksom ökad livslängd. AGRIMAX TURF RT 333 (R-3+) besitter enastående självrensande egenskaper och det låga rullmotståndet bidrar till betydande bränslebesparingar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Skördemaskin för fruktodling • Liten traktor • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	480/70 R 28
LI/SS	140 A8 / 140 B

## Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1421
Static Loaded Radius (mm)	631
Rolling Circumference (mm)	4228
SRI (mm)	650
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-009049

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1375	1600	1825	2050	2275	2500
40	1375	1600	1825	2050	2275	2500
30	1475	1715	1955	2195	2435	2675
10 LT	1845	2145	2450	2750	3050	3350
10 HT	1475	1715	1955	2195	2435	2675

Printed on 5/21/2024 7:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..