

## AGRIMAX TURF RT 333 - Ladda ned faktablad



### Description

AGRIMAX TURF RT 333 (R-3+) är ett radialdäck designat för små traktorer som används till trädgårdsskötsel, i fruktodlingar och på vingårdar. Den rundade däcksuldran ger låg jordpackning och gör däckets skonsamt mot marken. Det unika, extra djupa däcktäcket (R-3+) och specialdesignen med riktat mönster ger utmärkt dragförmåga på både åkern och vägen, liksom ökad livslängd. AGRIMAX TURF RT 333 (R-3+) besitter enastående självrensande egenskaper och det låga rullmotståndet bidrar till betydande bränslebesparingar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Skördemaskin för fruktodling • Liten traktor •  
Skördemaskin för vingård

| SIZE        | Version  | USACode  | TRA Code | LI/SS          | RIM REC | RIM ALT         | SW   | OD   | SLR  | RC    | Type | ECE             |
|-------------|----------|----------|----------|----------------|---------|-----------------|------|------|------|-------|------|-----------------|
| 220/55 R12  | STANDARD | 94070237 |          | 82 A8/B        | W7      |                 | 8.7  | 21.7 | 9.8  | 64.8  | TL   | E11-106R-007600 |
| 240/60 R12  | STANDARD | 94070657 |          | 89 A8/B        | W7      |                 | 9.5  | 23.3 | 10.6 | 70    | TL   | E11-106R-007679 |
| 200/65 R16  | STANDARD | 94070640 |          | 94 A8/B        | W6      |                 | 8    | 26.2 | 12.2 | 78.7  | TL   | E11-106R-007678 |
| 200/70 R 16 | STANDARD | 94074136 | R1W      | 94 A8/B        | W 6     |                 | 7.9  | 27   | 12.5 | 80.9  | TL   | E11-106R-008659 |
| 240/70 R16  | STANDARD | 94070282 |          | 104 A8/B       | W8      | W 8 L ; W 9     | 9.6  | 29.2 | 13.4 | 87.1  | TL   | E11-106R-007531 |
| 260/70 R 16 | STANDARD | 94067909 |          | 109 A8/109 B   | W 8     | W 8 L ; W 9     | 10.2 | 30.3 | 13.7 | 90    | TL   | E11-106R-007158 |
| 280/70 R 16 | STANDARD | 94065714 |          | 112 A8/112 B   | W9      | W 8 ; W 10      | 11.4 | 31.5 | 14.1 | 93.3  | TL   | E11-106R-006472 |
| 280/70 R 18 | STANDARD | 94065707 |          | 114 A8/114 B   | W 9     | W 8 ; W 10      | 11.4 | 33.1 | 15.4 | 100.4 | TL   | E11-106R-006473 |
| 320/65 R 18 | STANDARD | 94071081 |          | 109 A8/109 B   | W 10    | W 9 ; W 11      | 12.6 | 34.4 | 15.5 | 102   | TL   | E11-106R-007844 |
| 300/70 R 20 | STANDARD | 9406748  |          | 110 A8/110 B   | W9      | W10             | 11.6 | 37.5 | 17   | 111.3 | TL   | E11-106R-006943 |
| 320/70 R 20 | STANDARD | 94067558 |          | 113 A8/113 B   | W10     | W9 ; W11        | 12.6 | 38.7 | 17.4 | 114.8 | TL   | E11-106R-006944 |
| 380/70 R 20 | STANDARD | 94068821 |          | 122 A8/122 B   | W 12    | W 11 ; W 13     | 15   | 42.6 | 19.1 | 126.5 | TL   | E11-106R-007111 |
| 360/70 R 24 | STANDARD | 94067916 |          | 122 A8/122 B   | W 11    | W 10 ; W 12     | 14.1 | 45.4 | 20.4 | 134.2 | TL   | E11-106R-007110 |
| 380/70 R 24 | STANDARD | 94068838 |          | 125 A8/125 B   | W 12    | W 11 ; W 13     | 15   | 46.9 | 21   | 139.3 | TL   | E11-106R-007112 |
| 420/70 R 24 | STANDARD | 94069460 |          | 130 A8 / 130 B | W 13    | W 12 ; W 14 L   | 16.5 | 49.1 | 21.9 | 146.8 | TL   | E11-106R-007206 |
| 480/70 R 28 | STANDARD | 94075393 |          | 140 A8 / 140 B | W 15 L  | W 14 L ; W 16 L | 18.9 | 55.9 | 24.8 | 166.5 | TL   | E11-106R-009049 |
| 480/70 R 30 | STANDARD | 94075409 |          | 141 A8 / 141 B | W 15 L  | W 14 L ; W 16 L | 18.9 | 58.2 | 26   | 173.1 | TL   | E11-106R-009050 |
| 480/70 R 34 | STANDARD | 94075232 |          | 149 A8 / 149 B | W 15 L  | W 14 L ; W 16 L | 18.9 | 62.2 | 28.5 | 188.4 | TL   | E11-106R-009042 |

Printed on 5/21/2024 7:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..