

EARTHMAX SR 44 - Tekniska specifikationer



Description

EARTHMAX SR 44 (E-4) är ett stålradialdäck som passar en mängd olika användningsområden, till exempel i gruvor, vid vägtransporter och skogsavverkning. Det robusta E-4-slitbanemönstret ger både utmärkt dragkraft och hög komfort för föraren. EARTHMAX SR 44 (E-4) hjälper dig att optimera produktiviteten oberoende av användningsområde.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Väg- och terränggående lastbil

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 12.00 R 20 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94052295 |
| Overall Width (inch) | 12 |
| Overall Diameter (inch) | 44.8 |
| Static Loaded Radius (inch) | 20.9 |
| Rolling Circumference (inch) | 134.2 |
| Rim Rec | 8.50V |
| Rim Alt | 9.00V |
| Star Rating | *** |
| TRA Code | E4 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 112 |
| 30 | 9170 |

Printed on 5/21/2024 5:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..