

## TR 463 - Tekniska specifikationer



### Description

TR 463 är ett däck för traktorgrävare och industritraktorer. Den överlägsna gummiblandningen i slitbanan och det kraftiga nylonhöljet ger det här däckets bästa möjliga resultat i industri- och OTR-tillämpningar samt vid bygg- och anläggningsarbete. TR 463 ger utmärkt dragkraft på drivhjulen.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Grävlastare • Traktor

Version	INDUSTRIAL
Type	TL
Tyre Size	18.4 - 26
LI/SS	156 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	480
Overall Diameter (mm)	1425
Static Loaded Radius (mm)	637
Rolling Circumference (mm)	4215
SRI (mm)	675
Rim Rec	DW 16 L
Rim Alt	DW 15 L
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.50
40	4000

Printed on 5/21/2024 4:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..