

XL GRIP (BHL) - Tekniska specifikationer



Description

XL GRIP (BHL) är ett däck för traktorgrävare som används för tyngre gräv-, schaktnings- och lastningsarbeten. Det symmetriska slitbanemönstret ger högsta möjliga dragkraft och stabilitet. Den speciella gummiblandningen i slitbanan ger ett utmärkt skydd mot skär- och skrapskador och ger däckets en längre livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Grävlastare

| | |
|--------------------|--------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 12.5/80 - 18 |
| LI/SS FREE ROLLING | 142 A8 |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94050307 |
| Ply Rating | 12 |
| Section Width (inch) | 12 |
| Overall Diameter (inch) | 38.6 |
| Rim Rec | W 9 |
| Rim Alt | 11 |

Load capacity (lbs)

| | mph / psi | 54 |
|-------|-----------|------|
| 5 FR | | 8180 |
| 15 FR | | 6960 |
| 20 FR | | 6550 |
| 25 FR | | 5840 |

Printed on 5/21/2024 7:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..