

## XL GRIP (BHL) - Tekniska specifikationer



### Description

XL GRIP (BHL) är ett däck för traktorgrävare som används för tyngre gräv-, schaktnings- och lastningsarbeten. Det symmetriska slitbanemönstret ger högsta möjliga dragkraft och stabilitet. Den speciella gummiblandningen i slitbanan ger ett utmärkt skydd mot skär- och skrapskador och ger däckets en längre livslängd.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industri: Grävlastare

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	132 A6

## Dimensions US Standard

Usa code	94051267
Ply Rating	12
Section Width (inch)	10.2
Overall Diameter (inch)	35.8
Rim Rec	6.50 H
Rim Alt	6.00 G

## Load capacity (lbs)

mph / psi	83
20	4410

Printed on 21/05/2024 06:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..