

XL GRIP (L3) - Tekniska specifikationer



Description

XL GRIP (E-3/L-3) är ett diagonaldäck med bred bas för hjullastare. Det är utformat för att vara extra motståndskraftigt mot skärskador och punkteringar vid tillämpningar med tunga laster. Det har exceptionell dragkraft och extra lång livslängd.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Hjullastare

OTR: Bulldozer • Hjullastare

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	680
Overall Diameter (mm)	1740
Static Loaded Radius (mm)	796
Rolling Circumference (mm)	5150
Rim Rec	22.00/3.0
TRA Code	L3

Load capacity (Kg)

km/h / bar	4.75
10	15500

Printed on 5/21/2024 8:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..