

AT 625 - Teknik Özellikler



Description

AT 625 çiftçilik alanındaki tüm kazı ve yükleme faaliyetlerinde ters kepçe yükleyiciler ve kompakt damperli kamyonlarla kullanım için uygundur. Ekstra derin diş deseni, delinmeye karşı artırılmış dayanıklılık ve sağlamlık sunar. AT 625 kusursuz çekiş ve istikrarın yanı sıra kesilme ve parçalanmalara karşı gelişmiş dayanıklılığa sahiptir.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Bekoloder • Küçük yükleyici

Version	INDUSTRIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	152 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	450
Overall Diameter (mm)	1415
Static Loaded Radius (mm)	645
Rolling Circumference (mm)	4254
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.60
40	3550

Printed on 5/21/2024 8:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..