

## EARTHMAX SR 484 - Teknik Özellikler



### Description

EARTHMAX SR 484, özellikle açık maden işletmesi uygulamalarındaki taşıma operasyonlarına yönelik olan sabit kaya kamyonları için tasarlanmış, Tamamen Çelikten yapılmış bir radyal lastiktir. Geliştirilmiş çekiş ve kendiliğinden temizlenme özellikleri ile birlikte, kayalık ve sert koşullarda mükemmel koruma sağlayan özel sırt hamuru ile benzersiz bir E-3 sırt tasarımına sahiptir. Çok katmanlı çelik kuşaklara sahip Tamamen Çelik yapısı, çalışma süresini artırmak ve daha yüksek üretkenlik için şok, yorgunluk ve kaya delmelerine karşı üstün koruma sağlar. EARTHMAX SR 484, mükemmel manevra kabiliyeti ve sabitleme için zemin temasını en üst düzeye çıkaran kare omuz tasarımına sahiptir. Bu BTK lastiği özellikle daha yüksek hızlar ve uzun mesafeler için tasarlanmıştır.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Sabit kaya kamyonu

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

## Dimensions US Standard

Usa code	94067817
TMPH	360
Overall Width (inch)	28.9
Overall Diameter (inch)	104.2
Static Loaded Radius (inch)	47
Rolling Circumference (inch)	317.1
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Printed on 5/21/2024 3:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..