

FL 630 ULTRA - Teknik Özellikler



Description

FL 630 ULTRA; römorklar, tankerler ve yayıcılar için uygundur. Güçlendirilmiş damağı ve özel sırt tasarımı sayesinde her türlü arazide veya yolda çok amaçlı kullanım için ideal lastiktir. FL 630 ULTRA olağanüstü derecede daha az toprak sıkışması anlamına gelir.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Yayıcı • Tanker • Römork

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 710/50 R 26.5 |
| LI/SS | 170 D/181 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 727 |
| Overall Diameter (mm) | 1383 |
| Static Loaded Radius (mm) | 599 |
| Rolling Circumference (mm) | 4208 |
| SRI (mm) | 650 |
| Rim Rec | AG 24.00 |
| Rim Alt | AG 20.00 |
| ECE | E11-106R-006812 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|-------|
| 70 | 1750 | 1995 | 2240 | 2785 | 3170 | 3660 | 4150 | 4535 | 4970 | 5460 |
| 65 | 1920 | 2190 | 2460 | 3060 | 3480 | 4020 | 4560 | 4980 | 5460 | 6000 |
| 50 | 2325 | 2650 | 2980 | 3705 | 4210 | 4865 | 5520 | 6025 | 6610 | 7260 |
| 40 | 2640 | 3015 | 3385 | 4210 | 4785 | 5530 | 6270 | 6850 | 7510 | 8250 |
| 25 | 3035 | 3465 | 3890 | 4835 | 5500 | 6355 | 7205 | 7870 | 8630 | 9480 |
| 10 | 3460 | 3945 | 4430 | 5510 | 6265 | 7240 | 8210 | 8965 | 9830 | 10800 |

Printed on 5/20/2024 11:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..