

RIDEMAX IT 697 (M+S) - Veri Sayfasını İndir



Description

RIDEMAX IT 697 M+S kışın yapılan çalışmalar sırasında modern çiftçilik yüklenicilerinin ihtiyaçlarını karşılamak için en iyi yanıttır. Nakliye ve belediye uygulamaları için mükemmeldir. Traktörlerde kullanılan bu kış lastiği, kar zincirleri takmaya gerek kalmadan buzlu ve karlı yollardaki tüm çalışmalarda sıra dışı bir yol tutuş sağlar. Sirt kanalları ve güçlü gövdesi sayesinde, traktör yüksek hızlarda da tam sabitleme ile sürülebilir. Sirt tasarımı, ağır hizmetler için özel olarak geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

| SIZE | Version | USACode | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | TMPH | ECE |
|------------------------|----------|----------|---------------|---------|-------------------|------|------|------|-------|------|------|------------------|
| 460/70 R 24 IND | STANDARD | 94067039 | 157A8/152D | DW 15 L | DW14 L ; DW 16L | 18.3 | 49.4 | 22.5 | 148.5 | TL | 0 | E11-106R-006840 |
| 540/70R24 IND | STANDARD | 94072910 | 170D/175A8 | DW 16 L | DW18 L | 21.1 | 53.9 | 24.6 | 164.6 | TL | 0 | E11-106R-007933 |
| 480/65 R 28 IND | STANDARD | 94062720 | 149 D/154 A8 | DW 15 L | DW 14 L ; DW 16 L | 18.9 | 52.6 | 24.2 | 160.9 | TL | 0 | E11-106R-006159 |
| 540/65 R28 IND | STANDARD | 94055401 | 155 D/160 A8 | W 16 L | W 18 | 20.9 | 55.6 | 25.3 | 168.3 | TL | 0 | E11-106R-004076 |
| 600/65 R 28 IND | STANDARD | 94066995 | 165 A8/160 D | W 18 L | DW 20 B | 23.3 | 58.7 | 26.9 | 177.5 | TL | 0 | E11-106R-006760 |
| 540/65 R 30 IND | STANDARD | 94048106 | 156 D/161 A8 | W 16 L | W 18 | 20.9 | 57.6 | 26.5 | 175 | TL | 0 | E11-106R-003015 |
| 600/70 R 30 IND | STANDARD | 94058037 | 166 D/171 A8 | DW 18 L | DW 20 B | 23.6 | 63 | 27.1 | 189.8 | TL | 1 | E11-106R-005177 |
| 600/65 R 38 IND | STANDARD | 94062812 | 166 D/170 A8 | DW 18 L | DW 20 B | 23.2 | 68.7 | 31.3 | 209.3 | TL | 0 | E11-106R-005855 |
| 650/65 R 38 IND | STANDARD | 94055418 | 170 D/175 A8 | DW 20 B | DW 18 L | 25.4 | 71.3 | 32.4 | 217.1 | TL | 1 | E11-106R-004078 |
| 650/85 R 38 IND | STANDARD | 94066322 | 178 D/ 183 A8 | DW 23 B | DW 20 B ; DW 21 B | 27.9 | 81.5 | 38.3 | 247.2 | TL | 0 | E11-106R-006761 |
| 710/70 R 38 IND | STANDARD | 94067084 | 177D / 182A8 | DW 23 B | DW 25 B | 28.2 | 77.1 | 35.4 | 234.3 | TL | 0 | E11-106R-006762 |
| 650/65 R 42 IND | STANDARD | 94050109 | 171 D/176 A8 | DW 20 B | DW 18 L | 25.4 | 75.6 | 34.6 | 231.1 | TL | 0 | E4-106R-002659 |
| 710/70 R 42 IND | STANDARD | 94058099 | 180 D/185 A8 | DW23 B | | 28.2 | 81.4 | 36.5 | 246.6 | TL | 1 | 'E11-106R-005178 |

Printed on 5/21/2024 8:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..