

XL GRIP (BHL) - Teknik Özellikler



Description

XL GRIP (BHL) kazma, hafriyat ve yükleme uygulamalarındaki ağır yük gerektiren çalışmalarda kullanılan ters kepçe yükleyiciler için özel olarak tasarlanmıştır. Doğrusal olmayan diş deseni en iyi çekiş gücünü ve istikrarı sağlar. Özel diş bileşimi, kesilme ve parçalanmaya karşı kusursuz dayanıklılık ve daha uzun sırt ömrü sunar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Bekoloder

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	320
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	3710
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	8.25	8.25
10	6900	-
40	-	4830

Printed on 5/21/2024 1:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..