

## XL GRIP (L3) - Teknik Özellikler



### Description

XL GRIP (E-3/L-3) ağır yük gerektiren yükleme uygulamalarında kesilme ve delinmeleri en aza indirmek üzere tasarlanmış, yükleyicilere yönelik geniş tabanlı, çapraz kuşaklı bir lastiktir. Uzun bir lastik ömrü ile birlikte, sıra dışı çekiş gücü sağlar.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Endüstriyel: Yükleyici

Yoldışı: Dozer • Yükleyici

Version

STANDARD

Type

TL

Tyre Size

23.5 - 25

## Dimensions US Standard

Usa code	94015870
Ply Rating	20
Overall Width (inch)	23.6
Overall Diameter (inch)	64
Static Loaded Radius (inch)	29.2
Rolling Circumference (inch)	189.4
Rim Rec	19.50/2.5
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	44	54
30	16100	-
5	-	24000

Printed on 5/20/2024 10:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..