

## AGRIMAX TERIS - Technical Specifications



### Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	620/75 R 26 CHO
LI/SS	166 A8/B

## Dimensions International Standard

Section Width (mm)	625
Overall Diameter (mm)	1590
Static Loaded Radius (mm)	730
Rolling Circumference (mm)	4851
SRI (mm)	750
Rim Rec	DW 20 B
ECE	E4-106R-001419

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	2440	2810	3445	3765	4135	4505	4880	5300
40	2440	2810	3445	3765	4135	4505	4880	5300
30	2615	3010	3690	4030	4430	4825	5225	5675
15 Cyc	4025	4635	5685	6210	6825	7435	8050	8745
10 Cyc	4390	5060	6205	6775	7445	8110	8780	9540

Printed on 5/21/2024 5:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..