

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	650/75 R 32 CHO
LI/SS	172 A8/B

Dimensions International Standard

Section Width (mm)	670
Overall Diameter (mm)	1795
Static Loaded Radius (mm)	816
Rolling Circumference (mm)	5378
SRI (mm)	850
Rim Rec	DW 21 B
Rim Alt	DW 20 B ; DW 23 B
ECE	E4-106R-001425

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	2900	3340	4095	4475	4915	5355	5800	6300
40	2900	3340	4095	4475	4915	5355	5800	6300
30	3105	3575	4385	4790	5265	5735	6210	6745
15 Cyc	4785	5510	6760	7385	8110	8840	9565	10395
10 Cyc	5220	6015	7375	8055	8850	9640	10435	11340

Printed on 5/21/2024 8:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..