

# **EARTHMAX SR 55 - Data Sheet**



## **Description**

EARTHMAX SR 55 is an All Steel radial tire specially designed for loaders, dozers and load haul dumps operating in the most severe underground mining operations, and at scrapyards. Thanks to excellent cut protection resulting from the extra-deep and smooth tread design, EARTHMAX SR 55 is able to achieve peak productivity with reduced downtime along with excellent durability. Equipment operators will also appreciate extraordinary stability and traction.

#### UM

International Standard

#### Construction



### **Machinery**

OTR: Dozer • Load Haul Dump (LHD) • Loader

| SIZE       | Version                | TRA Code | Star R | LI/SS  | RIM REC   | RIM ALT              | OW  | OD   | SLR | RC   | Type |
|------------|------------------------|----------|--------|--------|-----------|----------------------|-----|------|-----|------|------|
| 12.00 R 24 | CUT RESISTANT COMPOUND | L5S      | **     | 175 A2 | 8.50/1.3  | 8.0,9.0              | 305 | 1274 | 572 | 3787 | TT   |
| 12.00 R 24 | CUT RESISTANT COMPOUND | L5S      | **     | 175 A2 | 8.50/1.3  | 8.0,9.0              | 305 | 1274 | 572 | 3787 | TL   |
| 17.5 R 25  | CUT RESISTANT COMPOUND | L5S      | **     | 182 A2 | 14.00/1.5 |                      | 453 | 1399 | 630 | 4211 | TL   |
| 17.5 R 25  | CUT RESISTANT COMPOUND | L5S      | ***    | 188 A2 | 14.00/1.5 |                      | 453 | 1399 | 630 | 4211 | TL   |
| 18.00 R 25 | CUT RESISTANT COMPOUND | L5S      | **     | 204 A2 | 13.00/2.5 |                      | 513 | 1667 | 733 | 4852 | TL   |
| 20.5 R 25  | CUT RESISTANT COMPOUND | L5S      | **     | 193 A2 | 17.00/2.0 |                      | 535 | 1543 | 700 | 4644 | TL   |
| 26.5 R 25  | CUT RESISTANT COMPOUND | L5S      | **     | 209 A2 | 22.00/3.0 |                      | 690 | 1786 | 810 | 5375 | TL   |
| 26.5 R 25  | CUT RESISTANT COMPOUND | L5S      | ***    | 214 A2 | 22.00/3.0 |                      | 690 | 1786 | 810 | 5375 | TL   |
| 29.5 R 25  | CUT RESISTANT COMPOUND | L5S      | **     | 216 A2 | 25.00/3.5 |                      | 777 | 1912 | 860 | 5755 | TL   |
| 29.5 R 29  | CUT RESISTANT COMPOUND | L5S      | **     | 218 A2 | 25.00/3.5 | 24.00/3.5, 26.00/3.5 | 775 | 2009 | 911 | 6047 | TL   |
| 35/65 R 33 | CUT RESISTANT COMPOUND | L5S      | ***    | 229 A2 | 28.00/3.5 |                      | 900 | 2065 | 915 | 6175 | TL   |
| 35/65 R 33 | CUT RESISTANT COMPOUND | L5S      | **     | 224 A2 | 28.00/3.5 |                      | 900 | 2065 | 915 | 6175 | TL   |

#### Printed on 5/20/2024 10:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..