

# MULTIMAX MP 522 - Technical Specifications



## Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Compact Loader • Telehandler  
Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	400/70 R 24 IND
LI/SS	152 A8/B

## Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	533
Rolling Circumference (mm)	3527
SRI (mm)	575
Rim Rec	13
Rim Alt	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L
ECE	E11-106R-002964

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1705	2025	2310	2630	2950	3160	3550	-	-
40	1705	2025	2310	2630	2950	3160	3550	-	-
30	1825	2170	2470	2815	3155	3385	3800	-	-
25	1895	2250	2565	2920	3275	3515	3945	-	-
10 Cyc.	2080	2560	3010	3465	3945	4290	4850	5115	5325
Static	3185	3920	4615	5310	6045	6575	7435	7840	8165

Printed on 5/21/2024 4:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..