

## RIDEMAX FL 693 M - Technical Specifications



### Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	710/35 R 22.5
LI/SS	157 D/154 E

## Dimensions International Standard

Section Width (mm)	712
Overall Diameter (mm)	1070
Static Loaded Radius (mm)	482
Rolling Circumference (mm)	3254
SRI (mm)	525
Rim Rec	AG 24.00
ECE	E11-106R-004758

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1370	1540	1915	2175	2515	2850	3115	3415	3750
65	1510	1695	2105	2395	2765	3135	3425	3755	4125
50	1825	2050	2550	2900	3350	3800	4150	4550	4995
40	2050	2305	2865	3255	3760	4265	4660	5110	5610
30	2275	3555	3180	3615	4175	4735	5175	5670	6230
25	2380	2675	3330	3785	4370	4960	5415	5935	6520
10	2715	3045	3790	4310	4975	5645	6165	6760	7425

Printed on 5/21/2024 7:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..