

RIDEMAX IT 697 (M+S) - Technical Specifications



Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	540/65 R28 IND
LI/SS	155 D/160 A8

Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1413
Static Loaded Radius (mm)	642
Rolling Circumference (mm)	4276
SRI (mm)	675
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E11-106R-004076

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1820	2250	2635	3060	3450	3875
50	1965	2425	2845	3305	3725	4185
40	2115	2610	3060	3555	4005	4500
30	2185	2695	3160	3675	4140	4650

Printed on 5/21/2024 7:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..