

# RIDEMAX IT 697 (M+S) - Technical Specifications



## Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	650/85 R 38 IND
LI/SS	178 D/ 183 A8

## Dimensions International Standard

Section Width (mm)	709
Overall Diameter (mm)	2071
Static Loaded Radius (mm)	974
Rolling Circumference (mm)	6280
SRI (mm)	975
Rim Rec	DW 23 B
Rim Alt	DW 20 B ; DW 21 B
ECE	E11-106R-006761

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	3525	4350	5100	5925	6675	7500
50	3805	4700	5510	6400	7210	8100
40	4115	5075	5950	6915	7790	8750
30	4230	5220	6120	7110	8010	9000

Printed on 5/21/2024 2:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..