

XL GRIP (L3) - Technical Specifications



Description

XL GRIP (E-3/L-3) is a wide-base bias-ply tire for loaders designed to minimize cuts and punctures in heavy-duty loading applications. It provides exceptional traction as well as an extended tire life.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Loader

OTR: Dozer • Loader

Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	600
Overall Diameter (mm)	1625
Static Loaded Radius (mm)	742
Rolling Circumference (mm)	4810
Rim Rec	19.50/2.5
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	2.25	3.00
50	6150	-
10	-	9500

Printed on 5/21/2024 12:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..