

# AGRIMAX SPARGO - Technical Specifications



## Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 380/105 R 54
LI/SS	180 D

## Dimensions International Standard

Section Width (mm)	400
Overall Diameter (mm)	2140
Static Loaded Radius (mm)	984
Rolling Circumference (mm)	6503
SRI (mm)	1050
Rim Rec	W 13 A
Rim Alt	W 12 ; DW 12 ; DW 13 ; DW 13 L
ECE	E11-106R-0010148
TRA Code	R1

## Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
70	3495	3930	4295	4515	4730	4875	5020	5275	5530	5750	5970	6330	6405	6550	6695	6985	7275
from 65 to 40	3840	4320	4720	4960	5200	5360	5520	5800	6080	6320	6560	6960	7040	7200	7360	7680	8000
30	3920	4410	4815	5060	5305	5470	5635	5920	6205	6450	6695	7100	7185	7345	7510	7835	8160
20	3995	4495	4910	5160	5410	5575	5745	6035	6325	6575	6825	7240	7325	7490	7655	7990	8320
10	4225	4755	5195	5460	5720	5900	6075	6380	6690	6955	7220	7660	7745	7920	8100	8450	8800

Printed on 5/21/2024 5:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..