

# AGRIMAX SPARGO - Technical Specifications



## Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 380/90 R 50
LI/SS	175 D

## Dimensions US Standard

Usa code	94065264
Section Width (inch)	15.4
Overall Diameter (inch)	76.8
Static Loaded Radius (inch)	35.2
Rolling Circumference (inch)	234.3
Rim Rec	W13 B
Rim Alt	W12 B
ECE	E11-106R-006400
TRA Code	R1

## Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	51	64
45	6640	7470	8160	8580	8990	9260	9540	10100	10510	10930	11350	11750	12030	12450	12720	13280	13840
From 40 to 25	7300	8220	8980	9430	9890	10190	10500	11100	11560	12020	12470	12930	13230	13690	13990	14600	15220
20	7450	8370	9150	9620	10080	10390	10700	11330	11790	12250	12710	13180	13500	13960	14270	14890	15510
12	7590	8540	9330	9800	10280	10600	10920	11550	12020	12490	12970	13440	13760	14240	14550	15180	15820
5	8030	9030	9870	10380	10870	11210	11550	12220	12710	13220	13720	14220	14550	15060	15390	16060	16740

Printed on 5/21/2024 12:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..