

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 520/85 R 42 |
| LI/SS | 168 D |

Dimensions International Standard

| | |
|----------------------------|----------------------------------------------------|
| Section Width (mm) | 516 |
| Overall Diameter (mm) | 1951 |
| Static Loaded Radius (mm) | 890 |
| Rolling Circumference (mm) | 5851 |
| SRI (mm) | 925 |
| Rim Rec | DW 16 L |
| Rim Alt | W15L ; DW15L ; DD16L ; W16L ; DD18L ; DW18L ; W18L |
| ECE | E4-106R-001829 |

Load capacity (Kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.8 |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 65 | 1850 | 2185 | 2520 | 2800 | 3140 | 3420 | 3980 | 4540 | 5100 | 5600 | - |
| 50 | 1945 | 2295 | 2650 | 2940 | 3295 | 3590 | 4175 | 4765 | 5355 | 5880 | - |
| 40 | 2025 | 2395 | 2765 | 3070 | 3440 | 3745 | 4360 | 4970 | 5585 | 6135 | - |
| 30 | 2130 | 2515 | 2900 | 3220 | 3610 | 3930 | 4575 | 5250 | 5865 | 6440 | - |
| 25 | 2195 | 2590 | 2990 | 3320 | 3720 | 4055 | 4715 | 5380 | 6045 | 6640 | - |
| 10 | 2775 | 3280 | 3780 | 4200 | 4705 | 5125 | 5965 | 6805 | 7645 | 8400 | - |
| 10 Cyc* | - | - | - | - | - | - | - | - | - | - | 9520 |

* - * 10 Cyc application inflation pressure to be increased by 0.8 bar.

Printed on 5/20/2024 10:36 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..