

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	710/55 R 28 CHO
LI/SS	164 A8/B

Dimensions US Standard

Usa code	94060023
Section Width (inch)	28.2
Overall Diameter (inch)	58.8
Static Loaded Radius (inch)	26.1
Rolling Circumference (inch)	174.9
Rim Rec	DW 23 B
ECE	E11-106R-005940

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	4300	4960	5620	6390	7050	7830	8710	9370	10250	11020
25	4300	4960	5620	6390	7050	7830	8710	9370	10250	11020
20	4610	5310	6020	6840	7550	8380	9330	10030	10980	11790
10 Cyc	7100	8190	9280	10550	11640	12920	14370	15460	16920	18190
5 Cyc	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840

Printed on 5/10/2024 10:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..