

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 38 NRO
LI/SS	166 D

## Dimensions US Standard

Usa code	94062119
Section Width (inch)	25.6
Overall Diameter (inch)	68.7
Static Loaded Radius (inch)	30.5
Rolling Circumference (inch)	205.9
Rim Rec	DW 23 B
Rim Alt	DW 21 B
Narrow Rim option	DW 20 B
ECE	E11-106R-005712
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	5840	6790	7750	8710	9670	10630
from 40 to 25	6430	7470	8520	9580	10630	11685
20	6550	7620	8690	9770	10840	11920
12	6680	7770	8850	9950	11040	12150
5	7070	8210	9370	10530	11680	12850
*Upto 5 Cyc with front loader	8990	10460	11930	13400	14870	16360
5 HT	6550	7620	8690	9770	10840	11920

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 5/10/2024 2:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..