

AGRIMAXFACTOR - Technical Specifications



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of evehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

US Standard

Construction

🐺 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Туре	TL
Tyre Size	710/70 R 38
LI/SS	166 D/169 A8

Dimensions US Standard

Usa code	94071142
Section Width (inch)	28.2
Overall Diameter (inch)	77.1
Static Loaded Radius (inch)	34.1
Rolling Circumference (inch)	228.3
Rim Rec	DW 23 B
ECE	E11-106R-007636
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	6430	7480	8530	9590	10640	11680
30	6760	7860	8960	10060	11170	12270
25	7040	8200	9350	10500	11650	12800
20	7400	8610	9810	11020	12230	13440
5 LT	8620	10030	11440	12850	14260	15660
5 HT	7400	8610	9810	11020	12230	13440

Printed on 5/20/2024 10:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..