

AT 625 - Technical Specifications



Description

AT 625 is suitable for backhoe loaders and compact loaders in all farming digging and loading operations. Its extra deep tread ensures increased puncture resistance and durability. AT 625 features excellent traction and stability as well as improved cut and chip resistance.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Backhoe Loader • Compact Loader

Version	STANDARD
Type	TT
Tyre Size	14.9 - 24
LI/SS	145 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	400
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3800
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13 L
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.90
40	2900

Printed on 5/20/2024 8:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..