

# EARTHMAX SR 25 PLUS - Technical Specifications



## Description

EARTHMAX SR 25 PLUS (G-2/L-2) is an All Steel radial tire, which has been specially designed for motor graders and loaders operating in the most severe road construction or mining applications. Its non-directional tread design offers excellent self-cleaning properties in addition to traction and stability off the road.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Industrial: Dozer • Grader • Loader

OTR: Dozer • Grader • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	153 A8/175 A2

## Dimensions US Standard

Usa code	94044962
Overall Width (inch)	14.1
Overall Diameter (inch)	54
Static Loaded Radius (inch)	24.6
Rolling Circumference (inch)	163.2
Rim Rec	8.00TG
Rim Alt	9.00GR
Star Rating	*
TRA Code	G2/L2

## Load capacity (lbs)

mph / psi	29	33	36	40	44	47	51	54	76	80
25	4940	5360	5840	6150	6600	7150	7400	8050	-	-
5	-	-	-	-	-	-	-	-	14800	15200

Printed on 5/9/2024 10:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..