

# **EARTHMAX SR 30 - Data Sheet**



# **Description**

EARTHMAX SR 30 (E-3/L-3) is an All Steel radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.

#### UM

**US Standard** 

### Construction



₩ RADIAL

# Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

| SIZE         | Version                   | USACode  | TRA<br>Code | Star<br>R | LI/SS           | RIM REC   | RIM ALT   | ow   | OD   | SLR  | RC    | Туре | ТМРН |
|--------------|---------------------------|----------|-------------|-----------|-----------------|-----------|-----------|------|------|------|-------|------|------|
| 15.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94052158 | E3/L3       | **/*      | 160 B/169<br>A2 | 12.00/1.3 | -         | 15.6 | 50.2 | 22.6 | 150   | TL   | 89   |
| 17.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94029112 | E3/L3       | **/*      | 167 B/176<br>A2 | 14.00/1.5 |           | 17.6 | 53   | 23.9 | 158.3 | TL   | 103  |
| 17.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94066315 | L3          | ***       | 188 A2          | 14.00/1.5 |           | 17.6 | 53   | 23.9 | 158.3 | TL   | 0    |
| 20.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94075256 | L3          | **        | 193 A2          | 17.00/2.0 | 17.00/1.7 | 20.8 | 58.5 | 26.1 | 174.8 | TL   | 0    |
| 20.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94027729 | E3/L3       | **/*      | 177 B/186<br>A2 | 17.00/2.0 | 17.00/1.7 | 20.8 | 58.5 | 26.1 | 174.8 | TL   | 116  |
| 23.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94026715 | E3/L3       | **/*      | 185 B/195<br>A2 | 19.50/2.5 |           | 24.1 | 63.3 | 28   | 188.9 | TL   | 137  |
| 26.5 R<br>25 | CUT RESISTANT COMPOUND    | 94028788 | E3/L3       | **/*      | 193 B/202<br>A2 | 22.00/3.0 |           | 27.1 | 68.6 | 30.2 | 204.7 | TL   | 158  |
| 26.5 R<br>25 | CUT RESISTANT COMPOUND    | 94054459 | E3          | **        | 193 B           | 22.00/3.0 |           | 27.1 | 68.6 | 30.2 | 204.7 | TL   | 158  |
| 26.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94054442 | L3          | *         | 202 A2          | 22.00/3.0 |           | 27.1 | 68.6 | 30.2 | 204.7 | TL   | 0    |
| 29.5 R<br>25 | CUT RESISTANT COMPOUND    | 94034291 | E3/L3       | **/*      | 200 B/208<br>A2 | 25.00/3.5 |           | 30.1 | 73.3 | 32.2 | 218.7 | TL   | 185  |
| 29.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94054466 | L3          | *         | 208 A2          | 25.00/3.5 |           | 30.1 | 73.3 | 32.2 | 218.7 | TL   | 0    |
| 29.5 R<br>25 | CUT RESISTANT<br>COMPOUND | 94054473 | E3          | **        | 200 B           | 25.00/3.5 |           | 30.1 | 73.3 | 32.2 | 218.7 | TL   | 185  |

#### Printed on 5/20/2024 11:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..