

EARTHMAX SR 44 - Technical Specifications



Description

EARTHMAX SR 44 is an **All Steel** radial tire suitable for a variety of applications including mining, haulage and logging applications. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) is able to optimize productivity whatever your operation is.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: On/Off Truck

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	146/143 G

Dimensions US Standard

Usa code	94045075
Ply Rating	16
Overall Width (inch)	10.6
Overall Diameter (inch)	42.3
Static Loaded Radius (inch)	19.9
Rolling Circumference (inch)	126
Rim Rec	7.50
Rim Alt	7.0 ; 7.50VM ; 8.0
ECE	E11-54R-0015908

Load capacity (lbs)

mph / psi	120
55	6600

Printed on 5/10/2024 8:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..