

# **EARTHMAX SR 46 - Data Sheet**



# **Description**

Earthmax SR 46 for rigid haul trucks is BKT's innovative response to severe rocky, abrasive and harsh mining environments. This tire has been specifically designed to carry heavy loads offering superior resistance to cuts and chips as well as a long tire life-cycle. The All Steel casing and belts provide extraordinary protection against shocks, fatigue and flats to maximize uptime and enhance productivity. Earthmax SR 46 features a special lug block pattern with circumferential groove to optimize the cornering performance with minimum tread face damage.

#### **UM**

**US Standard** 

### Construction



# Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	ow	OD	SLR	RC	Type	TMPH
27.00 R 49	CUT RESISTANT COMPOUND	94050161	E4	**	223 B	19.50/4.0	-	29.4	105.8	48.2	321.5	TL	312
27.00 R 49	HEAT RESISTANT COMPOUND	94055159	E4	**	223 B	19.50/4.0	-	29.4	105.8	48.2	321.5	TL	449
27.00 R 49	STANDARD COMPOUND	94050178	E4	**	223 B	19.50/4.0	-	29.4	105.8	48.2	321.5	TL	404
30.00 R 51	CUT RESISTANT COMPOUND	94074747	E4	**	230 B	22.00/4.5		32.9	114	51.2	346.5	TL	342
30.00 R 51	HEAT RESISTANT COMPOUND	94074723	E4	**	230 B	22.00/4.5		32.9	114	51.2	346.5	TL	497
30.00 R 51	STANDARD COMPOUND	94074754	E4	**	230 B	22.00/4.5		32.9	114	51.2	346.5	TL	418
33.00 R 51	CUT RESISTANT COMPOUND	94061723	E4	**	235 B	24.00/5.0		35.6	120.1	55.2	369.2	TL	382
33.00 R 51	HEAT RESISTANT COMPOUND	94067350	E4	**	235 B	24.00/5.0		35.6	120.1	55.2	369.2	TL	548
33.00 R 51	STANDARD COMPOUND	94065240	E4	**	235 B	24.00/5.0		35.6	120.1	55.2	369.2	TL	477

#### Printed on 5/10/2024 12:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..