

## FL 630 ULTRA - Technical Specifications



### Description

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Spreader • Tanker • Trailer

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 560/45 R 22.5 |
| LI/SS     | 152 D/163 A8  |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 543             |
| Overall Diameter (mm)      | 1076            |
| Static Loaded Radius (mm)  | 490             |
| Rolling Circumference (mm) | 3290            |
| SRI (mm)                   | 525             |
| Rim Rec                    | AG 16.00        |
| ECE                        | E11-106R-003012 |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70         | 1040 | 1185 | 1330 | 1650 | 1880 | 2170 | 2460 | 2690 | 2945 | 3235 |
| 65         | 1140 | 1300 | 1460 | 1815 | 2060 | 2380 | 2700 | 2950 | 3235 | 3550 |
| 50         | 1380 | 1575 | 1765 | 2195 | 2495 | 2885 | 3270 | 3570 | 3915 | 4300 |
| 40         | 1560 | 1780 | 2000 | 2490 | 2830 | 3270 | 3705 | 4050 | 4440 | 4875 |
| 30         | 1720 | 1960 | 2200 | 2740 | 3115 | 3595 | 4080 | 4455 | 4885 | 5365 |
| 25         | 1800 | 2055 | 2305 | 2865 | 3255 | 3760 | 4265 | 4660 | 5110 | 5610 |
| 10         | 2045 | 2335 | 2620 | 3260 | 3710 | 4285 | 4860 | 5305 | 5815 | 6390 |

Printed on 5/11/2024 1:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..