

FL 630 ULTRA - Technical Specifications

Description

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer



Version	STANDARD
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	165 D/176 A8

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1333
Static Loaded Radius (mm)	579
Rolling Circumference (mm)	4070
SRI (mm)	625
Rim Rec	AG 20.00
ECE	E11-106R-006813

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	1650	1910	2165	2630	3040	3505	3970	4275	4740	5150
50	2000	2310	2620	3180	3680	4240	4805	5180	5740	6235
40	2275	2630	2985	3625	4190	4830	5470	5895	6535	7100
25	2605	3015	3420	4155	4805	5540	6270	6760	7490	8140
10	2970	3435	3895	4730	5470	6305	7140	7695	8530	9270

Printed on 5/20/2024 10:45 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..