

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks.

Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction



Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Туре	TL
Tyre Size	500/50 R 17
LI/SS	149 D/146 E

Dimensions US Standard

Usa code	94045181
Section Width (inch)	19.8
Overall Diameter (inch)	36.7
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	114.7
Rim Rec	16.00
ECE	E4-106R-001821

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	73
45	2180	2450	2980	3370	3900	4430	4890	5360	5890	6610
40	2370	2660	3230	3660	4230	4810	5300	5810	6380	7160
30	2880	3220	3910	4430	5130	5820	6430	7030	7730	8670
25	3230	3620	4390	4970	5750	6540	7220	7900	8670	9740
15	3740	4190	5100	5780	6680	7590	8380	9170	10090	11320
5	4270	4770	5810	6580	7620	8640	9550	10450	11490	12900

Printed on 5/20/2024 10:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..