

RIDEMAX FL 693 M - Data Sheet



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
425/55 R17	STANDARD	129 D/140 A8	13.00		420	894	397	2704	425	TL	E11-106R-005104
500/50 R 17	STANDARD	149 D/146 E	16.00		503	932	424	2913	450	TL	E4-106R-001821
VF 500/50 R 17	STANDARD	156 D	16.00		503	932	422	2880	450	TL	E11-106R-007200
400/45 R 17.5	STANDARD	139 D	14.00		400	800	343	2357	390	TL	E11-106R-006619
VF 400/45 R 17.5	STANDARD	142 D	14.00		400	800	357	2448	390	TL	E11-106R-007199
500/45 R 22.5	STANDARD	146 D/143 E	AG 16.00		503	1022	455	3114	500	TL	E4-106R-000786
500/60 R 22.5	STANDARD	163 D	AG 16.00	15.00 ; 17.00	503	1172	544	3625	550	TL	E11-106R-007203
500/60 R 22.5	STANDARD	155 D/152 E	AG 16.00	15.00 ; 17.00	503	1172	531	3577	550	TL	E4-106R-001402
560/45 R 22.5	STANDARD	160D	AG 16.00		543	1076	491	3306	525	TL	E11-106R-009052
560/45 R 22.5	STANDARD	152 D/149 E	AG 16.00		543	1076	491	3306	525	TL	E4-106R-000629
560/55 R 22.5	STANDARD	162 D	AG 16.00	17.00 ; 20.00	543	1180	533	3614	550	TL	E11-106R-006972
560/55 R 22.5	STANDARD	158 D/155 E	AG 16.00	17.00 ; 20.00	543	1180	533	3614	550	TL	E4-106R-000631
560/60 R 22.5	STANDARD	169 D	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	552	3767	600	TL	E11-106R-006650
560/60 R 22.5	STANDARD	161 D/158 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	549	3767	600	TL	E4-106R-000630
560/60 R 22.5	STANDARD	165 D/162 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	552	3767	600	TL	E4-106R-001403
580/65 R 22.5	STANDARD	166 D/163 E	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	577	1326	572	4031	625	TL	E4-106R-000804
600/50 R 22.5	STANDARD	159 D/156 E	AG 20.00		611	1172	516	3574	550	TL	E4-106R-000805
650/50 R 22.5	STANDARD	163 D/160 E	AG 20.00		645	1222	535	3715	575	TL	E4-106R-001417
650/50 R 22.5	STANDARD	168 D	AG 20.00		645	1222	535	3715	575	TL	E11-106R-006489
710/35 R 22.5	STANDARD	157 D/154 E	AG 24.00		712	1070	482	3254	525	TL	E11-106R-004758
710/45 R 22.5	STANDARD	165 D	AG 24.00		706	1212	542	3658	575	TL	E11-106R-005994
600/55 R 26.5	HD	177 D	AG 20.00		611	1333	586	4077	625	TL	E11-106R-003007
600/55 R 26.5	STANDARD	165 D	AG 20.00		611	1333	586	4051	625	TL	E4-106R-002398
650/55 R 26.5	HD	178 D	AG 20.00		645	1389	615	4250	650	TL	E11-106R-003008
650/55 R 26.5	STANDARD	169 D	AG 20.00		645	1389	620	4216	650	TL	E4-106R-000806
710/50 R 26.5	HD	179 D	AG 24.00	AG 20.00	727	1383	606	4217	650	TL	E11-106R-006008
710/50 R 26.5	STANDARD	170 D	AG 24.00	AG 20.00	727	1383	624	4217	650	TL	E4-106R-001422
600/60 R 30.5	STANDARD	169 D	AG 20.00	AG 18.00	605	1495	681	4495	725	TL	E11-106R-006160
600/60 R 30.5	STANDARD	173 D	AG 20.00	AG 18.00	605	1495	681	4495	725	TL	E11-106R-007198
650/65 R 30.5	STANDARD	176 D	AG 20.00		645	1623	734	4939	775	TL	E11-106R-009076
710/50 R 30.5	STANDARD	173 D	AG 24.00	AG 20.00	727	1485	676	4533	700	TL	E4-106R-001498
750/60 R 30.5	STANDARD	181 D	AG 24.00		754	1675	728	5092	800	TL	E4-106R-001499
850/50 R 30.5	STANDARD	182 D	AG 28.00		862	1625	719	4925	725	TL	E4-106R-001500

Printed on 5/10/2024 1:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..