

RIDEMAX IT 696 - Technical Specifications



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavyduty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

International Standard

Construction



Machinery

Agriculture: Tractor

Version	STANDARD
Туре	TL
Tyre Size	400/80 R 24 IND (14.9 R 24)

LI/SS 149 A8/144 D

Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	558
Rolling Circumference (mm)	3760
SRI (mm)	600
Rim Rec	DW 13
Rim Alt	W 12; W 14 L
ECE	E4-106R-002400

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1315	1625	1905	2210	2490	2800
50	1440	1775	2080	2415	2725	3060
40	1530	1885	2210	2570	2895	3250
30	1590	1960	2300	2670	3010	3380

Printed on 5/21/2024 6:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..