

## RIDEMAX IT 696 - Technical Specifications



### Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	440/80 R 28 IND (16.9 R 28)
LI/SS	156 A8/151 D

## Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1415
Static Loaded Radius (mm)	634
Rolling Circumference (mm)	4288
SRI (mm)	675
Rim Rec	W 14 L
Rim Alt	W 15 L
ECE	E4-106R-002299

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1620	2000	2345	2725	3070	3450
50	1765	2180	2555	2970	3345	3760
40	1880	2320	2720	3160	3560	4000
30	1955	2415	2830	3285	3700	4160

Printed on 5/21/2024 12:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..