

RIDEMAX IT 696 - Technical Specifications



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	540/80 R 38 IND
LI/SS	172 A8/167 D

Dimensions US Standard

Usa code	94055838
Section Width (inch)	21.7
Overall Diameter (inch)	72
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	218
Rim Rec	W 18 L
Rim Alt	W 16 L
ECE	E11-106R-004077

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	5640	6970	8170	9490	10690	12010
30	6110	7530	8830	10260	11550	12980
25	6530	8060	9450	10970	12360	13890
20	7840	9670	11330	13160	14840	16670

Printed on 5/21/2024 6:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..