

## XL GRIP (BHL) - Technical Specifications



### Description

XL GRIP has been specially designed for backhoe loaders that are employed in heavy-duty operations in excavation, dozing and loading applications. The non-directional tread pattern provides best traction and stability. The special tread compound results in excellent cut and chip resistance and an extended tread life.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Backhoe Loader

Version	STANDARD
Type	TT
Tyre Size	12.5/80 - 18
LI/SS FREE ROLLING	148 A8

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	305
Overall Diameter (mm)	980
Rim Rec	W 9
Rim Alt	11

## Load capacity (Kg)

km/h / bar	4.90
10 FR	4410
25 FR	3750
30 FR	3530
40 FR	3150

Printed on 5/20/2024 8:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..