

XL GRIP PLUS - Technical Specifications



Description

XL GRIP PLUS (L-4) has been specially designed for loaders. Its deep tread provides high cut and puncture resistance as well as an extended tire life-cycle. XL GRIP PLUS is particularly suitable for heavy-duty service.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Dozer • Loader

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 29.5 - 25 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94059577 |
| Ply Rating | 36 |
| Overall Width (inch) | 29.9 |
| Overall Diameter (inch) | 75.4 |
| Static Loaded Radius (inch) | 34.5 |
| Rolling Circumference (inch) | 224.8 |
| Rim Rec | 25.00/3.5 |
| TRA Code | L4 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 83 |
| 5 | 46100 |

Printed on 5/20/2024 11:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..