

## I - 1 - Technische Daten



### Description

I-1 wurde für Feld- und Straßentransport sowie für die Bodenbearbeitung mit landwirtschaftlichen Geräten und Anhängern entworfen. I-1 ist ein Hochgeschwindigkeitsreifen, der Fahrtzeiten optimiert, sodass Sie sich auf Ihr Hauptgeschäft konzentrieren können. Das spezielle Laufflächenmuster gewährleistet ein langes Reifenleben auch unter harten Einsatzbedingungen und bei Stoppeln auf dem Feld.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TT
Tyre Size	10.0/75 - 15.3
LI/SS FREE ROLLING	118 D

## Dimensions US Standard

Usa code	94065202
Ply Rating	12
Section Width (inch)	10.6
Overall Diameter (inch)	30.1
Rim Rec	9.00
ECE	E11-106R-006267
TRA Code	I1

## Load capacity (lbs)

mph / psi	68
40	2910

Printed on 30.04.2024 16:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..