

## LG SMOOTH - Technische Daten



### Description

LG SMOOTH ist ein Reifen für Rasenflächen und Anwendungen im Gartenbau, der sich für Rasenmäher eignet. Während der Reifen sanft zu dem Boden ist, bietet das verbesserte Design verstärkte Beständigkeit und leichtes Handling. LG SMOOTH ist in Ausführung "aramid-belted" mit Aramidbändern erhältlich für Nutzer, die erhöhte Durchstichfestigkeit benötigen.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Rasenmäher • Kleintraktor

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 10

## Dimensions US Standard

Usa code	94013043
Ply Rating	6
Section Width (inch)	9.6
Overall Diameter (inch)	19.7
Static Loaded Radius (inch)	8.8
Rolling Circumference (inch)	57.1
Rim Rec	8.00 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005202

## Load capacity (lbs)

mph / psi	32
10	1455

Printed on 13.05.2024 18:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..