

## MP 590 - Technische Daten



### Description

MP 590 ist ein agro-industrieller Reifen für Ladearbeiten mit Teleskopladern und Gabelstaplern. Dieser Reifen verleiht gute Traktion und ausgezeichnete Stabilität sowie gesteigerte Beständigkeit.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Teleskoplader

Industrie: Gabelstapler • Teleskoplader • Universelles Fahrzeug

Version	STANDARD
Type	TL
Tyre Size	18 - 22.5 (445/65 - 22.5)

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Section Width (mm)</b>	480
<b>Overall Diameter (mm)</b>	1190
<b>Static Loaded Radius (mm)</b>	530
<b>Rolling Circumference (mm)</b>	3534
<b>Rim Rec</b>	14.0
<b>ECE</b>	E11-106R-004408

## Load capacity (Kg)

	km/h / bar	7.50
	40 DW	5800
	30 DW	6500

Printed on 13.05.2024 19:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..