

## MP 590 - Technische Daten



### Description

MP 590 ist ein agro-industrieller Reifen für Ladearbeiten mit Teleskopladern und Gabelstaplern. Dieser Reifen verleiht gute Traktion und ausgezeichnete Stabilität sowie gesteigerte Beständigkeit.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Teleskoplader

Industrie: Gabelstapler • Teleskoplader • Universelles Fahrzeug

Version	STANDARD
Type	TL
Tyre Size	18 - 22.5 (445/65 - 22.5)

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	480
Overall Diameter (mm)	1190
Static Loaded Radius (mm)	530
Rolling Circumference (mm)	3534
Rim Rec	14.0
ECE	E11-106R-003019

## Load capacity (Kg)

km/h / bar	5.50
40 DW	4875
30 DW	5450

Printed on 13.05.2024 17:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..