

AGRIMAX FORCE - Especificaciones técnicas



Description

AGRIMAX FORCE, el producto de punta de BKT, es un neumático radial específicamente proyectado para aplicaciones de tratamiento del terreno, de transporte y de cosecha con tractores y cosechadoras de elevada potencia, garantizando máximas prestaciones y eficiencia. Gracias a la tecnología IF, este neumático puede transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar reduciendo la compactación del suelo. AGRIMAX FORCE se caracteriza por la banda de rodadura reforzada y asegura una excelente tracción, elevadas propiedades de auto-limpieza y ahorros de carburante así como una conducción confortable.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora • Tractor de alta potencia

Version	STANDARD
Type	TL
Tyre Size	IF 620/75 R 30 CFO
LI/SS	169 D

Dimensions US Standard

Usa code	94064717
Section Width (inch)	25.6
Overall Diameter (inch)	67
Static Loaded Radius (inch)	29.9
Rolling Circumference (inch)	200.8
Rim Rec	DW 23 B
Rim Alt	DW 21 B
ECE	E11-106R-006496
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	5460	6270	7210	8130	9060	10000	10920	11630
From 40 to 25	6010	6900	7930	8950	9960	10990	12010	11355
20	6240	7180	8230	9300	10360	11420	12490	13290
12	6480	7450	8550	9660	10760	11860	12970	13800
5	7630	8760	10060	11360	12650	13950	15260	16240
Upto 20 Cyc	7800	8960	10300	11630	12950	14290	15620	16620
Upto 10 Cyc	9300	10690	12280	13870	15440	17030	18620	19820
Upto 5 Cyc	10210	11730	13470	15210	16930	18670	20420	21740
5 HT	6240	7180	8230	9300	10360	11420	12490	13290

Printed on 25/04/2024 0:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..