

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	650/65 R 30.5
LI/SS	176 D

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1623
Static Loaded Radius (mm)	734
Rolling Circumference (mm)	4939
SRI (mm)	775
Rim Rec	AG 20.00
ECE	E11-106R-009076

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2070	2395	2720	3300	3815	4400	4980	5370	5950	6465
65	2275	2630	2985	3625	4190	4830	5470	5895	6535	7100
50	2755	3185	3610	4385	5075	5845	6620	7135	7910	8595
40	3095	3580	4060	4930	5700	6570	7440	8020	8890	9660
25	3595	4155	4715	5725	6620	7630	8640	9315	10325	11220
10	4090	4730	5370	6520	7545	8695	9845	10610	11760	12780

Printed on 17/04/2024 5:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..