

TR 675 - Especificaciones técnicas



Description

TR 675 es un neumático diagonal especialmente diseñado para aplicaciones forestales. Su robusto diseño de tacos ofrece una tracción y una autolimpieza excelentes, mientras que la resistente estructura de la carcasa soporta cargas pesadas y sus cinturones de acero protegen el neumático de pinchazos y daños.

La TR 675 cuenta con un compuesto de banda de rodadura que brinda una excelente resistencia a los cortes y a las virutas incluso en terrenos difíciles en condiciones extremas.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Autocargadora

Version	STEEL BELTED
Type	TL
Tyre Size	540/65 - 28
LI/SS	155 A8/161 A2

Dimensions US Standard

Usa code	94059959
Ply Rating	16
Section Width (inch)	20.9
Overall Diameter (inch)	56.1
Static Loaded Radius (inch)	26.1
Rolling Circumference (inch)	174.8
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E11-106R-005271
TRA Code	LS2

Load capacity (lbs)

mph / psi	48
25	8550

Printed on 13/05/2024 15:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..