

TR 675 - Ficha técnica



Description

TR 675 es un neumático diagonal especialmente diseñado para aplicaciones forestales. Su robusto diseño de tacos ofrece una tracción y una autolimpieza excelentes, mientras que la resistente estructura de la carcasa soporta cargas pesadas y sus cinturones de acero protegen el neumático de pinchazos y daños.

La TR 675 cuenta con un compuesto de banda de rodadura que brinda una excelente resistencia a los cortes y a las virutas incluso en terrenos difíciles en condiciones extremas.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Autocargadora

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
540/65 - 28	STEEL BELTED	LS2	155 A8/161 A2	16	W 16 L	W 18 L	530	1425	663	4440	TL	E11-106R-005271

Printed on 13/05/2024 15:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..